

## **SPECIFICATIONS FOR SPRAYER (Item ID: 1000176364)**

- 1) 25 GALLON CAPACITY POLY TANK
- 2) 12-VOLT DIAPHRAGM PUMP HIGH-FLO PUMP, 2.1 GPM AND 60 psi
- 3) 5 INCH FILL LID
- 4) MOLDED DRAIN PORT WITH FULL DRAIN CAPABILITY
- 5) PISTOL GRIP HANDGUN WITH ADJUSTABLE NOZZLE
- 6) 15 FOOT HANDGUN HOSE

Acceptable Brands: Any brand which meets specs above.

**RUST PREVENTATIVE/RUST ENCAPSULANT/SALT NEUTRALIZER SPECIFICATIONS**

REV. 12/21

**SPECIFICATIONS FOR RUST PREVENTATIVE (ITEM 1000120026 AND 1000120027):**

ACCEPTABLE BRANDS: RHOMAR LUBRA SEAL OR EQUAL

- 1) ENCAPSULANT - HIGH-STRENGTH POLYMER WITH APPROPRIATE CHARGE TO ENCAPSULATE SALTS AND CHLORIDES
- 2) DRIED FLEXIBLE FILM THICKNESS - 2-3 MILS, NON-TACKY
- 3) ADDITIVE PACKAGE - E.P. AGENT, ANTI-RUST, ANTI-OXIDATION, CORROSION INHIBITOR
- 4) MOISTURE AND WATER RESISTANCE - INSOLUBLE, TOTALLY RESISTANT
- 5) ELEMENT RESISTANCE - HEAT, RAIN, WATER PRESSURE AND ACID
- 6) DRYING TIME - 60-120 MINUTES
- 7) API SPECIFIC GRAVITY - 7.5
- 8) VISCOSITY - SPRAYABLE LIQUID
- 9) FLASH POINT AND METHOD - >110 DEGREES F TCC
- 10) PACKAGING – 4/SIX GALLON PAILS AND 55 GALLON DRUMS

**SPECIFICATIONS FOR RUST PREVENTATIVE SPRAYER (ITEM 1000120028):**

ACCEPTABLE BRANDS/MODELS: RHOMAR, CHAPIN OR EQUAL

- 1) 3 GALLON CAPACITY
- 2) VITON SEALS AND GASKETS
- 3) BRASS NOZZLE AND ASSEMBLY WITH T-JET .5 GPM NOZZLE
- 4) BRASS SHUT OFF
- 5) HOSE IS TO BE ATTACHED AT THE FACTORY TO PREVENT HAZARDS OF ASSEMBLY
- 6) TANK - STEEL INTERIOR AND EXTERIOR COATED WITH TRI-POXY COATING

**SPECIFICATIONS FOR SALT NEUTRALIZER AND CHLORIDE REMOVER (ITEM 1000176362 AND ITEM 1000176363)**

ACCEPTABLE BRANDS: RHOMAR NEUTRO - WASH OR EQUAL

- 1) CHLORIDE REMOVAL – CALCIUM, MAGNESIUM AND SODIUM CHLORIDE LEAVING A SURFACE PH OF 6.5-7.5
- 2) ACTIVE INGREDIENT – ORGANIC SULFAMIC ACID
- 3) VAPOR PHASE INHIBITOR
- 4) WILL NOT HARM OIL WATER SEPERATORS
- 5) SPECIFIC GRAVITY – 1.02
- 6) WATER SOLUABLE

**RUST PREVENTATIVE/RUST ENCAPSULANT/SALT NEUTRALIZER SPECIFICATIONS**

REV. 12/21

- 7) NON-FLAMMABLE
- 8) PACKAGING – 6 GALLON PAILS AND 55 GALLON DRUMS

**SPECIFICATIONS FOR RUST ARRESTOR (ITEM 1000176365)**

ACCEPTABLE BRANDS: RHOMAR "BLACK MAX", KBS COATNGS MAXX OR EQUAL

- 1) ENCAPSULATES RUSTY SURFACE AND TRANSFORMS OXIDEZED RUST INTO PANTINA SURFACE.
- 2) SPECIFIC GRAVITY – 1.01
- 3) NON-FLAMMABLE
- 4) DRYING TIME – 3 TO 4 HOURS
- 5) CONVERTIVE BLEND – INVERSION POLYMERS
- 6) WATER SOLUBALE
- 7) VISCOSITY – SPRAYABLE OR BRUSH
- 8) PACKAGING – 4/ 1 GALLON CONTAINERS