



Tennessee Department of Safety and Homeland Security

34901-11932

Specifications

Brother PJ773 PocketJet 7 300dpi Full Page Thermal Printer w/Wi-Fi® & USB

Certifications

IP Certifications None

Communications

Communications Certifications: USB v2.0 (Full Speed) Wi-Fi 802.11/Direct/Infrastructure

Communications Interface(s): USB (Mini), WLAN

Communications Security: None

Compatibility

Operating System Compatibility: Windows 10 (32/64bit), Windows 8 (32/64bit), Windows (32/64bit), Windows Vista (32/64bit), Android v2.2 or later, Windows Server 2012 R2, Windows Server 2012, Windows Server 2008 R2, Windows Server 2008 (32/64bit), Mac OS X 10.10.x or later, Linux Red Hat and Debian

Print Driver Compatibility: Windows, Mac[®], Linux, Android, Windows Mobile

Consumables

Consumable Format Extended Cut Sheet, Fanfold Media, Roll with Continuous Media, Roll with Perforated Media, Roll with Die Cut Media

Consumable Max Roll OD Size Not Applicable

Consumable Roll Core ID Size Full Page Documents



Consumable Thickness	Not Published
Consumable Types	Full Page Documents
Media Width Max	8.5" (215.9mm)
Media Width Min	4 (Sensor 1.75" LoC)
<u>Dimensions</u>	
Unit Dimensions (W x D x H)	10.04" x 2.17" x 1.18" (255mm x 55mm x 30mm)
Unit Weight	1.25 lbs. (0.57kg) with Battery
<u>Environment Compatibility</u>	
Drop Protection	None
Operating Environment	14°F - 122°F (-10°C - 50°C)
Storage Environment	-4°F - 140°F (-20°C - 60°C)
<u>General</u>	
Available Color(s)	Black
Available Memory	6 MB
Channel Protected	Yes
Flash Memory	32MB
Media Exit Features	Tear Up
Media Feed Features	None
Media Feed Options	Drop In Roll, Adjustable Roll, Fanfold Holder
RAM	32MB
User Interface Data)	3 Switches (Power, Radio, Feed) 4 LEDs (Power, Radio, Feed,
<u>Power</u>	
Battery Charge Time	3 Hours
Battery Life	300 Cycles



Battery Required to Print	No
Battery Requirements	Rechargeable Li-ion Battery (PA-BT-002)
Battery Yield	600 Pages
Power Management	Auto Power On/Off
Power Source Options	AutoRanging Power Supply, Replaceable Rechargeable Battery, Vehicle Power Adapter, Forklift Power Adapter
Power Supply	15VDC 4.0A (PA-AD-600)

Print

Print Resolution	300 dpi
Print Speed	8ppm
Print Technology	Direct Thermal
Print Width Maximum	8.22" (208.8mm)
Printer Type	Portable

Print Features

2 Dimensional Barcodes	PDF417/MicroPDF417 Data Matrix Maxicode QR Code/Micro QR Code Aztec
Bitmap Fonts	Helsinki Brussels Letter Gothic
Borderless Printing‡	Yes
Emulations	Nonefmed
Linear Barcodes	Code39 Code93 Code128 ITF(I-2/5) UPC-A UPC-E EAN-8 EAN-13 GS1-128 (UCC/EAN-128) GS1 DataBar (RSS) MSI Industrial 2of5 Postnet
Media Sensor Types	Reflective (Black Bar, Hole) Out of Paper
Outline Fonts	Helsinki Brussels Letter Gothic
Print Commands	Raster_P ESC/P_P ESC/P_B P-touch Template
Stored Templates	Up to 256 templates



What's Included

Carton Configuration	Printer
Carton Contents	Printer, Battery Cavity Block, USB Cable, Printed Guides
Limited Warranty Length	1 Year
Warranty Type	Select Service

Thermal Paper

Thermal paper must have a minimum weight of 20 lbs

Thermal paper must have a minimum heat activation temperature of 155 degrees f.

Thermal paper must have at a minimum of 7 years and up to 20 years image retention expectance under proper archive conditions.

Thermal paper must be perforated roll paper.

Thermal paper must be able to accommodate 8.5 x 11" print.

Thermal paper must be water resistant.

Printers must be Brother PJ773 PocketJet 7 300dpi Full Page Thermal Printer w/Wi-Fi® & USB

Printer paper part number is LB3788