

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION
Qualified Products List Report



Parameters: **Product Category:** 16 - Pre-Packaged Grout
Approved Begin Date: 01/01/1990
Approved End Date: 01/01/2050
Display Expired Materials? No
Expired Begin Date: 01/01/1990
Expired End Date: 01/01/2050
Display Address Info For Sources: No

Product Category: 16 - Pre-Packaged Grout
Section: A- Pre-Packaged Grout
Material: QPL.16.001 - Pre-Packaged Grout

89901338 - Ash Grove Packaging

<u>Trade Name</u>	<u>Evaluation #</u>
Ash Grove Non-Shrink Grout	13056

Cementitious, non-shrink grout. Compressive strength, flowable: 2500 @ 1 day, 5500 @ 7 days, 7000 @ 28 days.

89900105 - BASF

<u>Trade Name</u>	<u>Evaluation #</u>
Emaco S-88CI	99150

Cementitious, "shrinkage-compensated" grout. Compressive strength, plastic: 4538 @ 1 day, 7884 @ 7 days, 10678 @ 28 days.

HB2 Repair Mortar	99164
-------------------	-------

Polymer-modified, non-shrink mortar. Compressive strength, 6000 @ 28 days.

Masterflow 928	99151
----------------	-------

Cementitious, non-shrink grout. Compressive strength, flowable: 4000 @ 1 day, 6700 @ 7 days, 8000 @ 28 days; plastic: 4500 @ 1 day, 7500 @ 7 days, 9000 @ 28 days.

Thoroc LA Repair Mortar	99165
-------------------------	-------

Cementitious grout. Compressive strength, plastic: 6075 @ 1 day, 7800 @ 7 days, 7900 @ 28 days.

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION
Qualified Products List Report



Product Category: 16 - Pre-Packaged Grout
Section: A- Pre-Packaged Grout
Material: QPL.16.001 - Pre-Packaged Grout

89901085 - Brave Industrial Supply

Trade Name
Silkabond Fastfill

Evaluation #
93149

Cementitious, non-shrink grout. Compressive strength, plastic: 4076 @ 1 day, 6521 @ 7 days, 7811 @ 28 days.

Silkabond Monomix Repair Mortar

93148

Polymer-modified non-shrink mortar. Compressive strength, 4940 @ 7 days, 6180 @ 28 days.

89901049 - Buzzi Unicem USA Inc

Trade Name
Ulti-Grout

Evaluation #
10030

Cementitious, non-shrink grout. Compressive strength, 3180 @ 1 hr., 7510 @ 1 day, >6000 @ 7 days, >7000 @ 28 days.

89900231 - CTS Cement Manufacturing Corp

Trade Name
Rapid Set DOT Repair Mix

Evaluation #
95057

Cementitious, non-shrink grout. Compressive strength, 4000 @ 1.5 hr., 5684 @ 1 day, 7364 @ 7 days, 8573 @ 28 days.

Rapid Set Non-Shrink Multipurpose Grout

95059

Cementitious, non-shrink grout. Compressive strength, 4800 @ 1 hr., 5200 @ 1 day, 8200 @ 7 days, 11200 @ 28 days.

89900171 - CeraTech Inc

Trade Name
Pavemend TR

Evaluation #
05050

Cementitious, non-shrink grout. Compressive strength, 1750 @ 1 hr., 5352 @ 1 day, 6147 @ 7 days, 7114 @ 28 days.

Pavemend VR

05051

Cementitious, non-shrink grout. Compressive strength, 4330 @ 1 hr., 5220 @ 1 day, 5880 @ 7 days, 6580 @ 28 days.

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION
Qualified Products List Report



Product Category: 16 - Pre-Packaged Grout
Section: A- Pre-Packaged Grout
Material: QPL.16.001 - Pre-Packaged Grout

89900183 - ChemMasters

Trade Name
Conset Grout

Evaluation #
01076

Cementitious, non-shrink grout. Compressive strength, plastic: 2775 @ 1 day, 6160 @ 7 days, 7150 @ 28 days; flowable: 2590 @ day, 5260 @ 7 days, 6870 @ 28 days; fluid: 2100 @ 1 day, 4920 @ 7 days, 6030 @ 28 days.

89900208 - Conspec

Trade Name
Conspec 100 N-S Grout

Evaluation #
99077

Cementitious, non-shrink grout. Compressive strength, flowable: 5000 @ 1 day, 8000 @ 7 days, 10000 @ 28 days; 3500 @ 1 day, 6500 @ 7 days, 8500 @ 28 days.

Conspec Enduro 50 Grout

99072

Cementitious, non-shrink grout. Compressive strength, dry pack: 5000 @ 1 day, 9000 @ 7 days, 10000 @ 28 days; flowable: 250 @ 1 day, 6000 @ 7 days, 8000 @ 28 days; fluid: 2000 @ 1 day, 5000 @ 7 days, 7500 @ 28 days.

Special Patch

99078

Polymer-modified, non-shrink grout. Compressive strength, neat: 1200 @ 3 hrs., 5200 @ 7 days, 7000 @ 28 days; extended: 400 @ 28 days.

89900215 - Cormix Construction Chemicals

Trade Name
Gilco Construction Grout

Evaluation #
93163

Cementitious, non-shrink grout. Compressive strength: 5986 @ 7 days, 6775 @ 28 days.

Supreme Non-Shrink Grout

93162

Cementitious, non-shrink grout. Compressive strength: 6821 @ 7 days, 7980 @ 28 days.

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION
Qualified Products List Report



Product Category: 16 - Pre-Packaged Grout
Section: A- Pre-Packaged Grout
Material: QPL.16.001 - Pre-Packaged Grout

89900246 - Dayton Superior

<u>Trade Name</u>	<u>Evaluation #</u>
1107 Advantage Grout	95099
Cementitious, non-shrink grout. Compressive strength: 2424 @ 1 day, 7460 @ 7 days, 8303 @ 28 days.	
Day-Chem Perma Patch	99107
Cementitious, non-shrink grout. Compressive strength: 2500 @ 1 hr., 5200 @ 1 day, 9000 @ 7 days, 10800 @ 28 days.	
HD-25 Polymer Modified Mortar	99107
Polymer-modified, non-shrink mortar. Compressive strength: 2400 @ 3 hrs., 3200 @ 1 day, 4100 @ 7 days, 5000 @ 28 days.	
HD-50 Concrete Patch	99108
Cementitious, non-shrink grout. Compressive strength, 2500 @ 1 hr., 6145 @ 1 day, 7370 @ 7 days, 7990 @ 28 days.	
Polyfast	93185
Polymer-modified, non-shrink mortar. Compressive strength: 1500 @ 3 hrs., 4000 @ 1 day, 6500 @ 7 days, 9000 @ 28 days.	
Sure Grip Grout	99106
Cementitious, non-shrink grout. Compressive strength: 5500 @ 1 day, 7500 @ 7 days, 10500 @ 28 days.	
Sure Grip HP/w Day Chem AD Bond	99109
Cementitious, non-shrink grout. Compressive strength, flowable: 5000 @ 1 day, 8000 @ 7 days, 10000 @ 28 days; fluid: 3500 @ day, 6500 @ 7 days, 8500 @ 28 days.	

89900308 - Edoco

<u>Trade Name</u>	<u>Evaluation #</u>
Burke Non-Ferrous Non-Shrink Grout	00010
Cementitious, non-shrink grout. Compressive strength, flowable: 5000 @ 1 day, 8000 @ 7 days, 10000 @ 28 days; fluid: 3500 @ 1 day, 6500 @ 7 days, 8500 @ 28 days.	

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION
Qualified Products List Report



Product Category: 16 - Pre-Packaged Grout
Section: A- Pre-Packaged Grout
Material: QPL.16.001 - Pre-Packaged Grout

89900343 - Euclid Chemical Co

<u>Trade Name</u>	<u>Evaluation #</u>
E3-Deep Pour	17088
Epoxy, non-shrink grout. Compressive strength: 11000 @ 1 day, 14000 @ 7 days, 15000 @ 28 days.	
E3-Flowable	17087
Epoxy, non-shrink grout. Compressive strength: 10000 @ 1 day, 12000 @ 7 days, 12500 @ 28 days.	
Euco NS Grout	04045
Cementitious, non-shrink grout. Compressive strength: 5000 @ 1 day, 7000 @ 7 days, 9000 @ 28 days.	
Hi-Flow Grout	04046
Cementitious, non-shrink grout. Compressive strength: 4000 @ 1 day, 7000 @ 7 days, 9000 @ 28 days.	
Tamms Structural Mortar	09109
Cementitious, non-shrink mortar. Compressive strength: 3200 @ 1 day, 6200 @ 7 days, 8500 @ 28 days.	
Verticoat	93175
Polymer-modified, non-shrink mortar. Compressive strength: 2622 @ 1 day, 4862 @ 7 days, 5102 @ 28 days.	

89900380 - Fox Industries Inc

<u>Trade Name</u>	<u>Evaluation #</u>
FX-228 Grout	91066
Cementitious grout. Compressive strength, stiff mix: 6000 @ 1 day, 9000 @ 7 days; flowable: 5800 @ 1 day, 8000 @ 7 days.	

89900453 - Hilti Inc

<u>Trade Name</u>	<u>Evaluation #</u>
Hilti Epoxy Grout	11121
Epoxy grout. Compressive strength: 3450 @ 8 hrs., 10450 @ 1 day, 13500 @ 7 days, >15000 @ 28 days.	
Hilti Multipurpose Grout	11104

* Material has been expired

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION
Qualified Products List Report



Product Category: 16 - Pre-Packaged Grout
Section: A- Pre-Packaged Grout
Material: QPL.16.001 - Pre-Packaged Grout

89900453 - Hilti Inc

Trade Name

Evaluation #

Cementitious, non-shrink mortar. Compressive strength: 4000 @ 1 day, 7000 @ 7 days, 7800 @ 28 days.

89900519 - Kaufman Products Inc

Trade Name

Evaluation #

Patchwell HB

99130

Polymer-modified, non-shrink mortar. Compressive strength: 3500 @ 1 day, 4000 @ 7 days, 5800 @ 28 days.

Patchwell Kit

99129

Polymer-modified, non-shrink mortar. Compressive strength: 1200 @ 1 day, 3200 @ 7 days, 4800 @ 28 days.

Sure Grout

99141

Cementitious, non-shrink mortar. Compressive strength: 6250 @ 1 day, 9000 @ 7 days, 10000 @ 28 days.

SureGrout 5000

21003

Cementitious, non-shrink grout. Compressive strength, plastic: 6000 @ 1 day, 9000 @ 7 days, 11000 @ 28 days; flowable: 6000 @ 1 day, 9000 @ 7 days, 11000 @ 28 days; fluid: 5000 @ 1 day, 8000 @ 7 days, 9000 @ 28 days.

89901477 - Pagel-USA

Trade Name

Evaluation #

V1/30 HF High Strength Non-Shrink Grout

17004

Cementitious, non-shrink grout. Compressive strength: 10150 @ 1 day, 13050 @ 7 days, 18850 @ 28 days.

V1/50 Non-Shrink Grout

17005

Cementitious, non-shrink grout. Compressive strength: 5800 @ 1 day, 10150 @ 7 days, 11600 @ 28 days.

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION
Qualified Products List Report



Product Category: 16 - Pre-Packaged Grout
Section: A- Pre-Packaged Grout
Material: QPL.16.001 - Pre-Packaged Grout

89900741 - Quikrete Co

<u>Trade Name</u>	<u>Evaluation #</u>
CG Fastset Non-Shrink Grout	03002
Cementitious, non-shrink grout. Compressive strength, plastic: 5000 @ 1 day, 6000 @ 7 days, 8000 @ 28 days; flowable: 4500 @ day, 5500 @ 7 days, 7500 @ 28 days; fluid: 4000 @ 1 day, 5000 @ 7 days, 6500 @ 28 days.	
Commercial Grade Fastset Repair Mortar	98055
Polymer-modified mortar. Compressive strength: 2000 @ 1 hrs., 3349 @ 1 day, 4912 @ 7 days, 5198 @ 28 days.	
Quick Setting Cement	92042
Cementitious grout. Compressive strength: 2201 @ 1 day, 5019 @ 7 days, 5312 @ 28 days.	

89900873 - STO Corp

<u>Trade Name</u>	<u>Evaluation #</u>
CR700 STO Thin Coat Mortar	91035
Polymer-modified concrete. Compressive strength: 5242 @ 7 days, 5697 @ 28 days.	
CR701 STO Trowel-Grade Mortar	91036
Polymer-modified, non-shrink mortar. Compressive strength: 3712 @ 1 day, 5926 @ 7 days, 6879 @ 28 days.	
CR702 STO Overhead Mortar	91034
Polymer-modified, non-shrink mortar. Compressive strength: 3113 @ 1 day, 5482 @ 28 days.	
CR730 STO Flowable Mortar	91033
Polymer-modified, non-shrink mortar. Compressive strength: 3920 @ 1 day, 5725 @ 7 days, 5751 @ 28 days.	

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION
Qualified Products List Report



Product Category: 16 - Pre-Packaged Grout
Section: A- Pre-Packaged Grout
Material: QPL.16.001 - Pre-Packaged Grout

89900836 - Sika Corp

<u>Trade Name</u>	<u>Evaluation #</u>
SikaGrout 212	05020
Cementitious, non-shrink grout. Compressive strength, plastic: 1500 @ 1 day, 5700 @ 7 days, 7500 @ 28 days; flowable: 1550 @ 1 day, 5500 @ 7 days, 6800 @ 28 days.	
SikaGrout 328	06001
Cementitious, non-shrink grout. Compressive strength, plastic: 4500 @ 1 day, 7000 @ 7 days, 8200 @ 28 days; flowable: 4000 @ 1 day, 6700 @ 7 days, 8200 @ 28 days.	
SikaGrout 428 FS	21006
Cementitious, non-shrink grout. Compressive strength, plastic: 4000 @ 1 day, 7500 @ 7 days, 11000 @ 28 days; flowable: 3500 @ 1 day, 7000 @ 7 days, 10500 @ 28 days; fluid: 3250 @ 1 day, 7500 @ 7 days, 10000 @ 28 days.	
Sikadur 42 Grout Pak LE	21007
Cementitious, non-shrink grout. Compressive strength: 5000 @ 24 hrs., 10000 @ 3 days, 11000 @ 7 days, 13300 @ 28 days.	

89900863 - SpecChem LLC

<u>Trade Name</u>	<u>Evaluation #</u>
SC Multipurpose Grout	07028
Cementitious, non-shrink grout. Compressive strength, plastic: 3500 @ 1 day, 7500 @ 7 days, 9500 @ 28 days; flowable: 3000 @ 1 day, 6500 @ 7 days, 8500 @ 28 days.	
Specplug	11091
Cementitious grout. Compressive strength, 1850 @ 1 hr., 3050 @ 1 day, 7650 @ 28 days.	

89900896 - Symons Corp

<u>Trade Name</u>	<u>Evaluation #</u>
Symons Fast Set 20	92040
Cementitious grout. Compressive strength, 390 @ 1 hr., 3000 @ 1 day, 5500 @ 7 days, 7500 @ 28 days.	

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION
Qualified Products List Report



Product Category: 16 - Pre-Packaged Grout
Section: A- Pre-Packaged Grout
Material: QPL.16.001 - Pre-Packaged Grout

89900896 - Symons Corp

Trade Name

Symons General Purpose Grout

Evaluation #

03015

Cementitious, non-shrink grout. Compressive strength, plastic: 5000 @ 1 day, 9000 @ 7 days, 10000 @ 28 days; flowable: 2500 @ 1 day, 6000 @ 7 days, 8000 @ 28 days; fluid: 2000 @ 1 day, 5000 @ 7 days, 7500 @ 28 days.

89900951 - Transpo Industries Inc

Trade Name

Silikal Polymer Concrete

Evaluation #

80035

Polymer-modified, non-shrink concrete. Compressive strength, 6000 @ 28 days.

Transpo T17

99158

Polymer-modified, non-shrink concrete. Compressive strength, 8000 @ 28 days.

89900983 - Universal Form Clamp Co

Trade Name

Patch Supreme Plus

Evaluation #

05071

Latex-modified, non-shrink mortar. Compressive strength: 1500 @ 3 hrs., 3500 @ 1 day, 5500 @ 7 days, 6500 @ 28 days.

Unigrout

06066

Cementitious, non-shrink grout. Compressive strength, plastic: 3500 @ 1 day, 7000 @ 7 days, 10600 @ 28 days; flowable: 3000 @ 1 day, 6500 @ 7 days, 8700 @ 28 days.

Unigrout Super

05070

Cementitious, non-shrink grout. Compressive strength, plastic: 4000 @ 1 day, 8500 @ 7 days, 11500 @ 28 days; flowable: 3500 @ 1 day, 7500 @ 7 days, 8500 @ 28 days.

Unipatch V/O

05072

Polymer-modified mortar. Compressive strength: 1500 @ 3 hrs., 3000 @ 1 day, 5000 @ 7 days, 6000 @ 28 days.

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION
Qualified Products List Report



Product Category: 16 - Pre-Packaged Grout
Section: A- Pre-Packaged Grout
Material: QPL.16.001 - Pre-Packaged Grout

89900996 - Vexcon Chemicals

<u>Trade Name</u>	<u>Evaluation #</u>
Certi-Grout 1000	92085
Cementitious, non-shrink grout. Compressive strength: 3992 @ 1 day, 5992 @ 7 days, 7951 @ 28 days.	
Certi-Grout 500	94014
Cementitious, non-shrink grout. Compressive strength: 2642 @ 1 day, 4430 @ 7 days, 6235 @ 28 days.	
Certi-Rapid Patch	95006
Polymer-modified, non-shrink mortar. Compressive strength: 2670 @ 3 hrs., 4770 @ 1 day, 6358 @ 7 days, 6772 @ 28 days.	

89901007 - W R Meadows Inc

<u>Trade Name</u>	<u>Evaluation #</u>
Sealtight 588 Non-Metallic Grout	99097
Cementitious, non-shrink grout. Compressive strength: 3183 @ 1 day, 6250 @ 7 days, 8008 @ 28 days.	
Sealtight CG-86 Construction Grout	99099
Cementitious, non-shrink grout. Compressive strength: 4200 @ 1 day, 6600 @ 7 days, 7800 @ 28 days.	
Sealtight Pac-It Non-Metallic Grout	99098
Cementitious, non-shrink grout. Compressive strength: 4291 @ 1 day, 9370 @ 7 days, 11138 @ 28 days.	

Number of Approved Materials in Report:

68