

AND


ST

9:47:29 AM raw\DESIGN

16/202

CATCH BASIN DIMENSIONS FOR DESIGN **USE ONLY** DIAMETER BOX SECTIO CATCH BASIN PIPE WALL OF CUT-OUT MINIMUM MINIMUM THICKNESS (D) OF PIPE HOLES HEIGHTS ESIGN DEPTI (INCHES) (INCHES) (INCHES) (INCHES) (FEET) $2\frac{1}{2}$ 25 4.24 32 4.79 30 $3\frac{1}{2}$ 39 78 5.33 46 5.87 4½ 53 6.41 42 60 6.95 54 67 106 7.50 $5\frac{1}{2}$ 74 113 8.04 81 120 8.58 88 127 9.12 95 9.66 134

- (1) CUT-OUT HOLES BASED ON REINFORCED CONCRETE PIPE WITH WALL TYPE "B"
- (2) ALL FLEXIBLE PIPE MATERIALS REQUIRE GASKET. SEE STANDARD DRAWING D-PB-2.
- (3) CUT-OUT HOLES FOR PRECAST STRUCTURES TO BE FORMED IN ORDER TO OBTAIN A SMOOTH EDGED HOLE. SCORED OR ETCHED HOLES WITH REINFORCING STEEL LEFT UNCUT WILL NOT BE PERMITTED.



GENERAL NOTES

- DRAWING TO BE USED FOR ALL CAST-IN-PLACE NO. 39SE CONCRETE CATCH BASINS AND ALL PRECAST NO. 39SE CONCRETE CATCH BASINS. SEE STANDARD DRAWING D-CB-99 FOR ADDITIONAL CONSTRUCTION NOTES & DETAILS
- THIS DRAWING DEPICTS THE MINIMUM HORIZONTAL REINFORCING AT THE TOP OF CATCH BASIN WALLS. SEE ADDITIONAL DETAILS ON STANDARD DRAWING D-CB-99 FOR TALLER SECTIONS AND STEEL PLACEMENT ABOVE PIPE OPENINGS.
- CAST-IN-PLACE CONCRETE CATCH BASINS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STANDARD SPECIFICATIONS, SECTION 611 AND/OR SPECIAL PROVISIONS UNLESS SUPERSEDED BY THIS DRAWING. THE CONTRACTOR MAY WITH PERMISSION FROM THE ENGINEER SUBSTITUTE PRECAST CATCH BASINS FOR CAST-IN-PLACE CATCH BASINS PROVIDED THAT ALL PRECAST ELEMENTS MEET ASTM C913 (CURRENT EDITION) UNLESS SUPERSEDED BY THIS DRAWING.
- THE FOLLOWING MATERIAL PROPERTIES ARE REQUIRED FOR BOTH CAST-IN-PLACE AND PRECAST STRUCTURES:

CONCRETE: f'c = 4,000 POUNDS PER SQUARE INCH AT 28 DAYS REINFORCING STEEL: ASTM A615, Fy = 60,000 POUNDS PER SQUARE INCH ALL REINFORCING IS TO BE INSTALLED AS DETAILED ON THIS DRAWING.

SECTION

- PRECAST CATCH BASIN UNITS WHICH ARE DAMAGED DURING SHIPMENT OR INSTALLATION WILL BE REJECTED. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO REPLACE DAMAGED CATCH BASIN UNITS AT THEIR OWN EXPENSE.
- APPROPRIATE SIZING AND LOCATION OF LIFTING DEVICES SHALL BE THE RESPONSIBILITY OF THE FABRICATOR.
- THE CONTRACTOR IS TO PATCH ALL LIFTING DEVICE HOLES WITH GROUT AND PLACE A MINIMUM OF ONE (1) INCH OF COVER OVER THE HARDWARE OF THESE DEVICES ON BOTH TOP AND BOTTOM SURFACES.
- ALTERNATIVE JOINT DETAILS MAY BE ACCEPTABLE. SEE STANDARD DRAWING D-CB-99 FOR ADDITIONAL
- SEE ROADWAY PLANS DRAINAGE TABULATION FOR PIPE INLET AND OUTLET ELEVATIONS. IF NEEDED, INVERT ELEVATIONS MAY BE ADJUSTED AS DIRECTED BY THE ENGINEER IN ORDER TO ACCOMMODATE INLET AND OUTLET
- FOR CASES WHERE THE OUTLET PIPE DIAMETER IS LARGER THAN THE INLET PIPE DIAMETER, A MINIMUM 24 $^{1}\!\!/_{2}$ INCH DEPTH SHALL BE MAINTAINED ABOVE THE OUTLET PIPE.
- CONCRETE JOINT MATERIAL TO BE $rac{1}{2}$ INCH PREMOLDED FIBER IN ACCORDANCE WITH SECTION 905 OF STANDARD SPECIFICATIONS, 4TH EDITION WITH INTERIMS.
- THE CONTRACTOR MAY ELIMINATE THE A502 BARS BY LENGTHENING THE VERTICAL LEG OF THE H500 BARS SO THAT 1½ INCHES OF CLEAR COVER IS PROVIDED AT THE TOP OF THE STRUCTURE.
- PAY DEPTH MEASUREMENT MADE FROM TOP OF GRATE TO OUTLET FLOW ELEVATION. PAYMENT INCLUDES GRATE, PAYMENT FOR CATCH BASIN WILL BE MADE UNDER ITEM NUMBERS:

611-39.02, CATCH BASINS, TYPE 39, > 4'-8' DEPTH, EACH (THROUGH) EACH.

611-39.07, CATCH BASINS, TYPE 39, > 24'-28' DEPTH,

WHEN CLASS "A" CONCRETE APRON IS USED, IT IS TO BE INCLUDED IN THE PRICE BID PER CATCH BASIN.

■ APPROVED BY FHWA (ALL OTHERS APPROVED BY TDOT)

STATE OF TENNESSEE STANDARD DRAWING DEPARTMENT OF TRANSPORTATION

REV. 7-29-02: CHANGED ASTM

STEEL IN BASE SECTION.

STEEL IN BASE SECTION.

SPECIFICATION IN GENERAL NOTE (C).

REV. 9-11-02: CHANGED REINFORCING

REV. 2-13-04: CHANGED REINFORCING

☐ REV. 8-01-12: REVISED CATCH BASIN FOR

DESIGN SPECIFICATIONS, 4TH EDITION

GENERAL NOTES, LEGEND AND

ADDITIONAL MISC. DRAFTING EDITS

REV. 3-11-14: ELIMINATED STIRRUPS

REV. 05-15-18: REVISED CATCH BASIN

CORRECTED STANDARD SPECIFICATIONS

-SHRINK GROUT. ADDED DIMENSION IN

CORRECTED REBAR PLACEMENT IN LIDS.

ADDED DIMENSION IN SECTION VIEW A-A

REV. 03-04-2021: REVISED GRATE UNIT NOTE

MINIMUM DESIGN DEPTH VALUES.

SECTION VIEW A-A FOR NOTE (J).

FOR MINIMUM DESIGN DEPTH.

REV. 02-20-2020: REDREW SHEET.

SECTION NUMBER TO 921 FOR NON

WITH INTERIMS. REVISED REINFORCING

COMPLIANCE WITH AASHTO LRFD BRIDGE

STANDARD 9' X 9' SQUARE CONCRETE NO. 39 **CATCH BASIN**

D-CB-39SE

12-18-1998