CONST. NO. _____

PROJECT NO.	YEAR	SHEET NO.

REVISIONS

NO.	DATE	BY	BRIEF DESCRIPTION

2 @ 16 x 13 REINFORCED CONCRETE BOX BRIDGE

	Maximum Fill Height ft.	Dimensions ST in.	SB in.	WT in.	IT in.	BW ft.	Bars TST Size	No.	Spacing in.	Length ft.	Bars TSB Size	No.	Spacing in.	Length ft.	Bars BST Size	No.	Spacing in.	Length ft.	Bars BSB Size	No.	Spacing in.	Length ft.	Bars EWE Size	No.	Spacing in.	Length ft.	Bar EWI Size	No.	Spacing in.	Length ft.	Bar IW Size	No.	Spacing in.	Length ft.	Bars LNT No.	Bars LND No.	Bars WS No.	Concrete CY/LF	Reinf. Steel LB/LF
Continuous	No Fill	10.5	9	8	8	34.00	10	1	12	33.50	9	1	12	33.50	7	1	12	34.50	9	1	12	34.50	4	2	12	13.00	8	2	12	13.00	4	4	6	13.00	180	32	6	3.03	801
	3	12	11	9	8	34.17	7	2	6	33.66	9	1	12	33.66	7	1	12	34.66	7	2	6	34.66	4	2	12	13.00	8	2	12	13.00	4	4	6	13.00	180	32	6	3.50	820
	5	12	12	8	8	34.17	11	1	12	33.66	8	1	12	33.66	8	1	12	34.66	11	1	12	34.66	4	2	12	13.00	9	2	12	13.00	4	4	6	13.00	214	0	6	3.61	909
	10	13	16	10	8	34.33	9	2	6	33.83	6	2	6	33.83	8	1	12	34.83	11	1	12	34.83	4	2	12	13.00	10	2	12	13.00	4	4	6	13.00	214	0	6	4.24	996
Moment Break	20	16	19	13	8	34.83	4	2	12	16.66	10	2	6	34.33	10	2	6	35.33	4	2	12	16.66	4	2	12	13.00	7	4	6	13.00	4	4	6	13.00	214	0	6	5.18	1025
	30	25	27	16	8	35.33	4	2	12	16.66	9	2	6	34.83	9	2	6	35.83	4	2	12	16.66	4	2	12	13.00	9	2	12	13.00	4	4	6	13.00	218	0	6	7.35	891
	40	31	33	18	8	35.67	4	2	12	16.66	9	2	6	35.16	9	2	6	36.16	4	2	12	16.66	4	2	12	13.00	9	2	12	13.00	7	2	12	13.00	218	0	6	8.91	914
	50	36	38	20	8	36.00	4	2	12	16.66	10	2	6	35.50	10	2	6	36.50	4	2	12	16.66	4	2	12	13.00	6	4	6	13.00	8	2	12	13.00	222	0	6	10.26	1057
	60	40	42	22	8	36.33	4	2	12	16.66	10	2	6	35.83	10	2	6	36.83	4	2	12	16.66	4	2	12	13.00	6	4	6	13.00	6	4	6	13.00	222	0	6	11.41	1071

2 @ 16 x 14 REINFORCED CONCRETE BOX BRIDGE

	Maximum Fill Height ft.	Dimensions ST in.	SB in.	WT in.	IT in.	BW ft.	Bars TST Size	No.	Spacing in.	Length ft.	Bars TSB Size	No.	Spacing in.	Length ft.	Bars BST Size	No.	Spacing in.	Length ft.	Bars BSB Size	No.	Spacing in.	Length ft.	Bars EWE Size	No.	Spacing in.	Length ft.	Bar EWI Size	No.	Spacing in.	Length ft.	Bar IW Size	No.	Spacing in.	Length ft.	Bars LNT No.	Bars LND No.	Bars WS No.	Concrete CY/LF	Reinf. Steel LB/LF
Continuous	No Fill	10.5	9	8	8	34.00	10	1	12	33.50	9	1	12	33.50	7	1	12	34.50	9	1	12	34.50	4	2	12	14.00	9	2	12	14.00	6	2	12	14.00	186	32	6	3.10	839
	3	12	11	9	8	34.17	7	2	6	33.66	9	1	12	33.66	7	1	12	34.66	7	2	6	34.66	4	2	12	14.00	9	2	12	14.00	6	2	12	14.00	186	32	6	3.58	858
	5	12	12	10	8	34.33	11	1	12	33.83	8	1	12	33.83	8	1	12	34.83	11	1	12	34.83	4	2	12	14.00	9	2	12	14.00	6	2	12	14.00	220	0	6	3.79	931
	10	13	16	11	8	34.50	9	2	6	34.00	6	2	6	34.00	8	1	12	35.00	11	1	12	35.00	4	2	12	14.00	11	2	12	14.00	6	2	12	14.00	220	0	6	4.43	1049
Moment Break	20	16	20	14	8	35.00	4	2	12	16.66	10	2	6	34.50	9	2	6	35.50	4	2	12	16.66	4	2	12	14.00	7	4	6	14.00	6	2	12	14.00	224	0	6	5.50	988
	30	25	27	17	8	35.50	4	2	12	16.66	9	2	6	35.00	9	2	6	36.00	4	2	12	16.66	4	2	12	14.00	9	2	12	14.00	6	2	12	14.00	224	0	6	7.59	913
	40	31	33	20	8	36.00	4	2	12	16.66	10	2	6	35.50	10	2	6	36.50	4	2	12	16.66	4	2	12	14.00	9	2	12	14.00	7	2	12	14.00	228	0	6	9.28	1003
	50	36	38	22	8	36.33	4	2	12	16.66	10	2	6	35.83	10	2	6	36.83	4	2	12	16.66	4	2	12	14.00	9	2	12	14.00	8	2	12	14.00	228	0	6	10.66	1090
	60	40	43	24	8	36.67	4	2	12	16.66	10	2	6	36.16	10	2	6	37.16	4	2	12	16.66	4	2	12	14.00	9	2	12	14.00	6	4	6	14.00	228	0	6	11.94	1105

2 @ 16 x 15 REINFORCED CONCRETE BOX BRIDGE

	Maximum Fill Height ft.	Dimensions ST in.	SB in.	WT in.	IT in.	BW ft.	Bars TST Size	No.	Spacing in.	Length ft.	Bars TSB Size	No.	Spacing in.	Length ft.	Bars BST Size	No.	Spacing in.	Length ft.	Bars BSB Size	No.	Spacing in.	Length ft.	Bars EWE Size	No.	Spacing in.	Length ft.	Bar EWI Size	No.	Spacing in.	Length ft.	Bar IW Size	No.	Spacing in.	Length ft.	Bars LNT No.	Bars LND No.	Bars WS No.	Concrete CY/LF	Reinf. Steel LB/LF
Continuous	No Fill	10.5	10	9	8	34.17	10	1	12	33.66	9	1	12	33.66	6	1	12	34.66	6	2	6	34.66	4	2	12	15.00	9	2	12	15.00	7	2	12	15.00	192	32	6	3.39	840
	3	12	11	10	8	34.33	7	2	6	33.83	9	1	12	33.83	7	1	12	34.83	7	2	6	34.83	4	2	12	15.00	9	2	12	15.00	7	2	12	15.00	192	32	6	3.76	892
	5	12	12	10	8	34.33	11	1	12	33.83	8	1	12	33.83	8	1	12	34.83	11	1	12	34.83	4	2	12	15.00	11	2	12	15.00	7	2	12	15.00	226	0	6	3.87	1019
	10	13	16	12	8	34.67	9	2	6	34.16	6	2	6	34.16	8	1	12	35.16	11	1	12	35.16	4	2	12	15.00	11	2	12	15.00	7	2	12	15.00	226	0	6	4.63	1087
Moment Break	20	16	20	15	8	35.17	4	2	12	16.66	10	2	6	34.66	9	2	6	35.66	4	2	12	16.66	4	2	12	15.00	11	2	12	15.00	7	2	12	15.00	230	0	6	5.72	1060
	30	25	28	18	8	35.66	4	2	12	16.66	9	2	6	35.16	9	2	6	36.16	4	2	12	16.66	4	2	12	15.00	7	4	6	15.00	7	2	12	15.00	230	0	6	7.95	967
	40	31	34	21	8	36.17	4	2	12	16.66	9	2	6	35.66	9	2	6	36.66	4	2	12	16.66	4	2	12	15.00	7	4	6	15.00	7	2	12	15.00	234	0	6	9.67	976
	50	36	39	24	8	36.67	4	2	12	16.66	10	2	6	36.16	10	2	6	37.16	4	2	12	16.66	4	2	12	15.00	9	2	12	15.00	8	2	12	15.00	234	0	6	11.20	1113
	60	40	43	26	8	37.00	4	2	12	16.66	10	2	6	36.50	10	2	6	37.50	4	2	12	16.66	4	2	12	15.00	9	2	12	15.00	6	4	6	15.00	238	0	6	12.38	1132

2 @ 16 x 16 REINFORCED CONCRETE BOX BRIDGE

	Maximum Fill Height ft.	Dimensions ST in.	SB in.	WT in.	IT in.	BW ft.	Bars TST Size	No.	Spacing in.	Length ft.	Bars TSB Size	No.	Spacing in.	Length ft.	Bars BST Size	No.	Spacing in.	Length ft.	Bars BSB Size	No.	Spacing in.	Length ft.	Bars EWE Size	No.	Spacing in.	Length ft.	Bar EWI Size	No.	Spacing in.	Length ft.	Bar IW Size	No.	Spacing in.	Length ft.	Bars LNT No.	Bars LND No.	Bars WS No.	Concrete CY/LF	Reinf. Steel LB/LF
Continuous	No Fill	10.5	10	10	8	34.33	10	1	12	33.83	9	1	12	33.83	6	1	12	34.83	6	2	6	34.83	4	2	12	16.00	9	2	12	16.00	8	2	12	16.00	198	32	6	3.58	879
	3	12	11	10	8	34.33	7	2	6	33.83	9	1	12	33.83	5	2	6	34.83	7	2	6	34.83	4	2	12	16.00	11	2	12	16.00	8	2	12	16.00	198	32	6	3.85	991
	5	12	12	11	8	34.50	11	1	12	34.00	8	1	12	34.00	8	1	12	35.00	11	1	12	35.00	4	2	12	16.00	11	2	12	16.00	8	2	12	16.00	232	0	6	4.07	1062
	10	13	16	13	8	34.83	9	2	6	34.33	6	2	6	34.33	8	1	12	35.33	11	1	12	35.33	4	2	12	16.00	11	2	12	16.00	8	2	12	16.00	232	0	6	4.84	1130
Moment Break	20	16	20	16	8	35.33	4	2	12	16.66	10	2	6	34.83	10	2	6	35.83	4	2	12	16.66	4	2	12	16.00	11	2	12	16.00	8	2	12	16.00	236	0	6	5.96	1167
	30	25	28	20	8	36.00	4	2	12	16.66	9	2	6	35.50	9	2	6	36.50	4	2	12	16.66	4	2	12	16.00	7	4	6	16.00	8	2	12	16.00	240	0	6	8.34	1011
	40	31	34	23	8	36.50	4	2	12	16.66	9	2	6	36.00	9	2	6	37.00	4	2	12	16.66	4	2	12	16.00	7	4	6	16.00	8	2	12	16.00	240	0	6	10.09	1018
	50	36	39	25	8	36.83	4	2	12	16.66	10	2	6	36.33	10	2	6	37.33	4	2	12	16.66	4	2	12	16.00	7	4	6	16.00	8	2	12	16.00	240	0	6	11.51	1156
	60	40	43	28	8	37.33	4	2	12	16.66	10	2	6	36.83	10	2	6	37.83	4	2	12	16.66	4	2	12	16.00	7	4	6	16.00	6	4	6	16.00	244	0	6	12.85	1178

Note: Maximum fill height shown in the table is measured from the bottom of the top slab. To obtain the total fill height from the flow line, add the height of the box.
Note: When top slab is the riding surface (No Fill), the concrete cover to the top mat of reinforcing shall be 2-1/2 inches.

The following bar information applies to all fill cases in the table above:
Bars LNT Size = 4 Spacing = 12 in.
Bars LND Size = 5 Spacing = 12 in.
Bars WS Size = 8 Length = 5.00 ft. Spacing = 12 in.

NOTE: FOR DESCRIPTIONS OF BOX DIMENSIONS AND REINFORCING BAR DESIGNATIONS SEE STANDARD DRAWING NO. STD-15-4.

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION

STANDARD REINFORCED CONCRETE BOX BRIDGE
INTERIOR SECTION
SPANS: 2 BARRELS AT 16'-0"
CLEAR HEIGHTS 13'-0" THRU 16'-0"
0' THRU 60' FILL
2000

CORRECT Edward P. Wasserman
ENGINEER OF STRUCTURES

STD-15-67

DESIGNED BY JOHN PHILLIPS DATE 1-00
DRAWN BY KEVIN MARTINKO DATE 3-00
SUPERVISED BY FIELDS & HOLLORAN DATE 3-00
CHECKED BY JOHN PHILLIPS DATE 6-00

D:\STD2000\15\2barrel_box16
15:57